



15.6" Multi Function Display



Astronautics' Avionics 15.6" Multi-Functional Display (MFD) is a large display to be used in cockpit main avionics displays, and for various sensors integration. The MFD includes a video matrix selector and a USB hub selector. Its excellent optical performance includes high brightness and contrast, high resolution, ultra-wide viewing angles and high ruggedization.

GENERAL FEATURES

- A full HD LCDs – IPS technology.
- Dual mode, NVIS compatible backlight
- High brightness and anti-reflection coating for direct view in sunlight.
- Control switches, illuminated and NVIS compatible.
- Selection of one out of 5 video inputs at any resolution.
- Communication with two HOST computers.
- USB HUB connects a mouse and a keyboard to one out of 5 computers.
- Highly ruggedized mechanical enclosure.
- Designed to meet stringent environmental and EMI Military Standards.





15.6" Multi Function Display

OPTICAL SPECIFICATION	
Display Area	13.5 inch x 7.6 inch (344 x 194 mm)
Resolution	FHD - 1920 x 1080 color pixels (RGB)
Luminance	Up to 300 FL.
Luminance Uniformity	75%
Viewing Angles	±80° horizontal and vertical
Contrast (no ambient light)	600:1 (No ambient light); 6 :1 minimum in 10,000fC diffused, plus 2000fL specular sunlight.
Shades of grey	256 per primary color (total of 16 M colors)
NVIS Compatibility	NVIS B Compliance
ELECTRICAL SPECIFICATIONS	
Video Interfaces	4 DVI Inputs at any standard resolution; 1 Analog RGB-HV at any standard resolution.
USB Hub	5 x USB 2.0 upstream Channels, 2 x USB 2.0 Downstream Channels.
Communication	2 Channels of serial RS422 communication
Power	28 Vdc at 60 W max (excluding heater operation)
MECHANICAL SPECIFICATIONS	
Dimensions	15.4 x 10.2 x 2.9 inches (391 x 259 x 73 mm) - excluding connectors.
Front panel	7 momentary illuminated pushbuttons and rocker, NVIS compatible
Power supply	28Vdc (MIL-STD-704A) at 60W max (without heater).
Weight	7 kg
Environmental Specifications	
Temperature - operating	-40°C to +55°C continuous; +70°C intermittent
Altitude	0 to 50,000 Feet
Others	Per MIL-STD-810 G / F (Vibration, Shock, Humidity, Rain, Salt-fog, Solar radiation, Fungus, Dust, Acoustic noise)
EMI/EMC	Per MIL-STD-461E

FOR MORE INFORMATION ON THIS OR ANY OF OUR OTHER PRODUCTS/SYSTEMS PLEASE CONTACT:

Astronautics C.A. Ltd., 16 Martin Ghel St., P.O.B 3351 Petah-Tikva 49130, Israel

Phone: (972)-3-9251555, Fax (972)-3-9251550, E-mail: astro@astro.co.il or visit our website www.astronautics.co.il